



DEEP GLOSS Maintainer for Stainless Steel

| HMIS | | NFPA | Personal protective equipment |
|-------------------------------|---|------|-------------------------------|
| Health | 1 | 1 | None / Aucune / Ninguno |
| Flammability | 4 | 4 | |
| Physical Hazard / Instability | 0 | 0 | |

Version Number: 1

Preparation date: 2012-03-29

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: DEEP GLOSS Maintainer for Stainless Steel

MSDS #: MS0300762

Product Code: 4970590

Recommended use: Specialty Cleaner . This product is intended to be used heat .

Manufacturer, importer, supplier:

US Headquarters
Diversey, Inc.
8310 16th St.
Sturtevant, Wisconsin 53177-1964
Phone: 1-888-352-2249
MSDS Internet Address: www.diversey.com

Canadian Headquarters
Diversey, Inc. - Canada
2401 Bristol Circle
Oakville, Ontario L6H 6P1
Phone: 1-800-668-3131

Emergency telephone number: 1-888-660-6737

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
DANGER: Aspiration into the lungs may cause chemical pneumonitis. HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE . CONTENTS UNDER PRESSURE. MAY BE MILDLY IRRITATING TO EYES. MAY BE MILDLY IRRITATING TO SKIN.

Principal routes of exposure: Skin contact. Inhalation. Eye contact.

Eye contact: May be mildly irritating to eyes.

Skin contact: May be mildly irritating to skin.

Inhalation: None known.

Ingestion: Aspiration into the lungs may cause chemical pneumonitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient(s) | CAS # | Weight % | LD50 Oral - Rat (mg/kg) | LD50 Dermal - Rabbit | LC50 Inhalation - Rat |
|-----------------------------------|------------|------------|-------------------------|----------------------|-----------------------|
| Isoparaffinic hydrocarbon solvent | 64742-48-9 | 10 - 20% | 5000 | >3160 mg/kg | Not available |
| Aliphatic hydrocarbons | 64742-47-8 | 20 - 30% | 5000 | >2000 mg/kg | >5.2 mg/L (4 h) |
| Silicones | 63148-62-9 | 5 - 10% | 16000 | >2 g/kg | Not available |
| White mineral oil | 8042-47-5 | 5 - 10% | 5000 | Not available | Not available |
| Alcohol ethoxylates | 34398-01-1 | 0.1 - 1.5% | 1000 | Not available | Not available |
| Liquified petroleum gas | 68476-86-8 | 20 - 30% | 2000 | Not available | Not available |

Hazardous components None

4. FIRST AID MEASURES

Eye contact: Flush immediately with plenty of water. If irritation develops, get medical attention.

Skin contact: Flush immediately with plenty of water. If irritation develops, get medical attention.

Inhalation: If breathing is affected, remove to fresh air.

Ingestion: Do not induce vomiting. Call medical attendant, medical doctor, or poison control center immediately.

Aggravated Medical Conditions: None known

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Dry chemical, water spray, foam, carbon dioxide.
Specific hazards: Aerosol product - Containers may rocket or explode in heat of fire. NFPA 30B Level 2 Aerosol.
Unusual hazards: None known
Specific methods: Aerosol Product - Containers may rocket or explode in heat of fire. Use water spray to keep fire-exposed containers cool.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use personal protective equipment.
Environmental precautions and clean-up methods: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling:
 CONTENTS UNDER PRESSURE. Do not puncture or incinerate. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin and eyes. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:
 NFPA 30B Level 2 Aerosol. Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 degrees C or 120 degrees F. Do not pierce or burn, even after use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:
 No special ventilation requirements General room ventilation is adequate

Personal Protective Equipment

Eye protection: No special requirements under normal use conditions.
Hand protection: No special requirements under normal use conditions
Skin and body protection: No special requirements under normal use conditions.
Respiratory protection: No special requirements under normal use conditions.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

| Ingredient(s) | CAS # | ACGIH | OSHA | Mexico |
|------------------------|------------|-------|------------------------|--------|
| Aliphatic hydrocarbons | 64742-47-8 | | 1200 mg/m ³ | |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| <p>Physical State: Aerosol Appearance: Aerosol Specific gravity: 0.81 Vapor density: No information available Boiling point/range: Not determined Decomposition temperature: Not determined Solubility: Insoluble Solubility in other solvents: No information available Partition coefficient (n-octanol/water): No information available Elemental Phosphorus: 0 % by wt. pH: No information available Flame Extension (inches): less than 18 Explosion limits: - upper: Not determined - lower: Not determined</p> | <p>Bulk density: No information available Evaporation Rate: No information available Color: Milky White Odor: Characteristic Melting point/range: Not determined Autoignition temperature: No information available Density: 6.76 lbs/gal 0.81 Kg/L Flash point: 120 °F 48.9 °C Viscosity: No information available VOC: 29 % * Dilution pH: No information available.</p> |
|--|---|

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability: The product is stable
Polymerization: Hazardous polymerization does not occur
Hazardous decomposition products: None reasonably foreseeable.
Conditions to avoid: Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Oral LD50 estimated to be between 4000 - 5000 mg/kg ; Dermal LD50 estimated to be > 2000 mg/kg
Component Information: See Section 3

Chronic toxicity: None known

Specific effects
Carcinogenic effects: None known
Mutagenic effects: None known
Reproductive toxicity: None known
Target organ effects: None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:
 Dispose of according to all federal, state and local applicable regulations. If possible, recycle empty aerosol cans to the nearest steel recycling center. Use up contents if possible before disposal. This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations.
RCRA Hazard Class: D001 Ignitable Waste

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, <http://naextranet.diversey.com/dot/>, for up to date shipping information.

DOT Bill of Lading Description: LTD. QTY.

IMDG Bill of Lading Description: UN1950, AEROSOLS, 2.1, LTD. QTY. (48.9°C(cc))

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

RIGHT TO KNOW (RTK)

| Ingredient(s) | CAS # | MARTK: | NJRTK: | PARTK: | RIRTK: |
|-----------------------------------|------------|--------|--------|--------|--------|
| Water | 7732-18-5 | - | - | - | - |
| Propane | 74-98-6 | X | X | X | - |
| Liquified petroleum gas | 68476-86-8 | - | - | - | - |
| Isoparaffinic hydrocarbon solvent | 64742-48-9 | - | - | - | - |
| Butane | 106-97-8 | X | X | X | - |
| Aliphatic hydrocarbons | 64742-47-8 | - | - | - | - |
| Silicones | 63148-62-9 | - | - | - | - |
| White mineral oil | 8042-47-5 | X | X | - | - |
| Alcohol ethoxylates | 34398-01-1 | - | - | - | - |

CERCLA/ SARA

None

SARA 311/312 Hazard Categories

| | |
|-----------------------------|---|
| Immediate: | X |
| Delayed: | - |
| Fire: | X |
| Reactivity: | - |
| Sudden Release of Pressure: | X |

Canada

WHMIS hazard class: A Compressed gases, B5 Flammable aerosol.



16. OTHER INFORMATION

| | |
|-----------------------------|--|
| Reason for revision: | Not applicable |
| Prepared by: | NAPRAC |
| Additional advice: | • This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations |

Notice to Reader. This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.